



WHY RUN WITH APACHE?

THE APACHE MODEL AS1030 SPRAYER

Comfort. Speed. Accuracy. Efficiency. That's exactly what you get from every Apache sprayer. They're built to handle the everyday (and not-so-everyday) field conditions with a higher standard of comfort and performance. And because all we do is build sprayers, we're 100% focused on building the best sprayers in the industry, backed by the best warranty in the industry.

With a 1,000-gallon capacity tank, the Apache AS1030 sprayer is the most popular sized model in the lineup. It features a mechanical drive that makes it simple to operate and nimble enough to work in field conditions competitive sprayers can't. It's 10,800 pounds lighter than a Deere R4038, reducing yield-robbing compaction. When the days are long, its 35 mph road speed will get you to the next field (or home) faster.

UNIQUE FEATURES OF THE AS1030

Tank Capacity

1,000 gallons

Transmission

ZF Power Shift, 6-speed with lock-up torque converter

Engine

Tier 4F 225 hp
Cummins engine

Top Road Speed

35 MPH

Weight

20,000 lbs (approx. dry weight)

Crop Clearance

42" with JCB planetary final drives
50" clearance with 18" drop box all-gear final drives (optional)



THE APACHE MODEL AS1030 SPRAYER

Specifications

| | |
|--|---|
| Tank Capacity | 1,000 gallons |
| Transmission | ZF Power Shift, 6-speed with lock-up torque converter |
| Engine | Tier 4F 225 hp Cummins engine |
| Top Road Speed | 35 MPH |
| Weight | 20,000 lb (approximate dry weight) |
| Crop Clearance | 42" with JCB planetary final drives 50" with 18" drop box all-gear final drives (optional) |
| Fuel Capacity | 90 gallons |
| DEF Tank | 5 gallons |
| Suspension | Patented independent hydraulic |
| Brakes | Fully-enclosed, self-adjusting, internal wet disc brakes |
| Front Tires | 380/80R38 (narrow and semi-float options available) |
| Rear Tires | 380/90R46 (narrow, semi-float and full-float options available) |
| Transport Width and Height | 144" maximum |
| Overall Length | 290" maximum |
| Booms | Custom boom straight 90' or 100' or 60'/90' Custom boom Pommier straight 120' or 132' |
| Product Pump | HYPRO® hydraulically-driven centrifugal product pump |
| Rinse Tank | 100 gallons |
| Cab | ET custom pressurized state-of-the-art interior and console |
| Precision Application Equipment | Raven Hawkeye™ or Trimble (factory installed) |

All model year 2017 Apache sprayers are available with optional ISOBUS-ready wiring in lieu of factory installed field computers. Refer to your specific precision agriculture product documentation for compatibility information. Equipment Technologies factory installs all field computers using CAN bus wiring and protocols.

