

# THE APACHE MODEL AS1230XP SPRAYER

Comfort. Speed. Accuracy. Efficiency. That's exactly what you get from every Apache Sprayer. They're built to handle the everyday (and not-so-everyday) field conditions with a higher standard of comfort and performance. Because all we do is build sprayers, we're 100% focused on building the best sprayers in the industry.

The Apache AS1230 XP Sprayer is the highest-capacity model in the lineup. It features a 1,200-gallon tank so you spend less time refilling and more time spraying. Its mechanical drive makes it simple to operate and maintain, while nimble enough to work in field conditions competitive sprayers can't. It's 14,300 pounds lighter than a Deere 4045, reducing yield-robbing compaction. When the days are long, its 35 mph road speed will get you to the next field (or home) faster.

## **UNIQUE FEATURES** OF THE AS1230

### **Tank Capacity** 1,200 gallons

#### **Transmission**

ZF Powershift, 6-speed with lock-up torque converter

#### **Engine**

Tier 4F 260 hp Cummins engine

# **Top Road Speed**

35 mph

#### Weight

21,000 lbs (approximate dry weight)

#### **Crop Clearance**

50" clearance with 18" drop box all-gear final drives





# THE APACHE MODEL AS1230 XP SPRAYER

ANK CAPACITY	1,200 gal
RANSMISSION	ZF Powershift, 6-speed with lock-up torque converter
UMMINS ENGINE	Tier 4F 300 hp AS1230 XP
OP ROAD SPEED	35 mph
UEL CAPACITY	90 gal
VEIGHT	21,000 lbs (approximate dry weight)
ROP CLEARANCE	50" clearance with 18" drop box all-gear final drives
DEF TANK	5 gal
USPENSION	Patented independent hydraulic
XEL WIDTH	120" fixed 120"- 160" adjustable
RAKES	Fully enclosed, self-adjusting, internal wet disc brakes
RONT TIRES REAR TIRES	Michelin® 380/80R38 (narrow and semi-float options available)
RANSPORT WIDTH AND HEIGHT	144" maximum
VERALL LENGTH	290" maximum
00MS	ET Custom Boom Straight 90' or 100' or 60'/90' Pommier Straight 100', 120' or 132'
RODUCT PUMP	Hypro® hydraulically-driven centrifugal product pump
INSE TANK	100 gal
T CUSTOM PRESSURIZED	State-of-the-art interior and console
RECISION APPLICATION EQUIPMENT	Raven Hawkeye™
	RANSMISSION  JMMINS ENGINE  DP ROAD SPEED  JEL CAPACITY  /EIGHT  ROP CLEARANCE  EF TANK  JSPENSION  KEL WIDTH  RAKES  RONT TIRES REAR TIRES  RANSPORT WIDTH AND HEIGHT  VERALL LENGTH  DOMS  RODUCT PUMP  NSE TANK  I CUSTOM PRESSURIZED

All model year 2018 Apache Sprayers are available with optional ISOBUS-ready wiring in lieu of factory installed field computers. Refer to your specific precision agriculture product documentation for compatibility information. Equipment Technologies factory installs all field computers using CAN-BUS wiring and protocols.

Equipment Technologies reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. All brand or product names are or may be trademarks of, and are used to identify products and services of, their respective owners or its subsidiaries and divisions. in the U.S. and/or other countries. All specifications are subject to change without notice.



