

EquipmentWatch.

**Highest
Retained Value
Award™**
2018

3x
Winner



AS730

THE APACHE MODEL AS730 SPRAYER

Comfort. Speed. Accuracy. Efficiency. That's exactly what you get from every Apache Sprayer. They're built to handle the everyday (and not-so-everyday) field conditions with a higher standard of comfort and performance. Because all we do is build sprayers, we're 100% focused on building the best sprayers in the industry.

The Apache AS730 Sprayer was engineered for the farmer looking for do-it-yourself control and peace of mind. Featuring a 750-gallon tank and mechanical drive, it's simple to operate and nimble enough to work in field conditions competitive sprayers can't. It's 10,100 pounds lighter than a Deere R4030, reducing yield-robbing compaction. When the days are long, its 30 mph road speed will get you to the next field (or home) faster.

UNIQUE FEATURES OF THE AS730

Tank Capacity

750 gallons

Transmission

JCB transmission
Powershift, 4-speed

Engine

Tier 4F 173 hp
Cummins engine

Top Road Speed

30 mph

Weight

19,700 lbs (approximate dry weight)

Crop Clearance

42" with JCB planetary final drives
50" clearance with 18" drop box
all-gear final drives (optional)

APACHE by **ET**
SPRAYERS

Learn more about the advantages of running with Apache! Visit your local Apache dealer or apachesprayers.com.

☎ 877-398-6164

THE APACHE MODEL AS730 SPRAYER

TANK	TANK CAPACITY	750 gal
ENGINE & DRIVETRAIN	TRANSMISSION	JCB transmission Powershift, 4-speed
	CUMMINS ENGINE	Tier 4F 173 hp
	TOP ROAD SPEED	30 mph
	FUEL CAPACITY	90 gal
CHASSIS, SUSPENSION & TIRES	WEIGHT	19,700 lbs (approximate dry weight)
	CROP CLEARANCE	42" with JCB planetary final drive 50" clearance with 18" drop box all-gear final drives (optional)
	DEF TANK	5 gal
	SUSPENSION	Patented independent hydraulic
	AXEL WIDTH	120" fixed 120" - 160" adjustable
	BRAKES	Fully enclosed, self-adjusting, internal wet disc brakes
	FRONT TIRES REAR TIRES	Michelin® 380/80R38 (narrow and semi-float options available)
	TRANSPORT WIDTH AND HEIGHT	144" maximum
	OVERALL LENGTH	290" maximum
	SPRAY OPTIONS	BOOMS
PRODUCT PUMP		Hypro® hydraulically-driven centrifugal product pump
RINSE TANK		100 gal
CAB	ET CUSTOM PRESSURIZED	State-of-the-art interior and console
	PRECISION APPLICATION EQUIPMENT	Raven Hawkeye™

All model year 2018 Apache Sprayers are available with optional ISOBUS-ready wiring in lieu of factory installed field computers. Refer to your specific precision agriculture product documentation for compatibility information. Equipment Technologies factory installs all field computers using CAN-BUS wiring and protocols.

Equipment Technologies reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. All brand or product names are or may be trademarks of, and are used to identify products and services of, their respective owners or its subsidiaries and divisions. in the U.S. and/or other countries. All specifications are subject to change without notice.



Learn more about the advantages of running with Apache! Visit your local Apache dealer or apachesprayers.com.

 877-398-6164