QUALITY TIRE OPTIONS

Michelin[®] Agriculture Tires come standard on all Apache Sprayers. We also offer alternative offers for narrows, duals and floats. Every tire used by Apache is inspected upon assembly to ensure farmers enjoy a long service life. We look for excellent traction and lateral stability with robust crowns and deep tread bars to coincide with our unmatched traction expectations.

AS640

OPTION	TYPE	SIZE	WIDTH	SERIES	MANUFACTURER
FRONT	STANDARD	380/85R34	15"	AGRIBIB	MICHELIN
FRONT	OPTIONAL	380/80R38	15"	AGRIBIB	MICHELIN
FRONT	NARROW	320/85R38	12.6"	DT800	GOODYEAR®
REAR	STANDARD	380/80R38	15"	AGRIBIB	MICHELIN
REAR	FLOTATION	620/70R42	24.4"	MEGAXBIB	MICHELIN
REAR	FLOTATION	800/65R32	31.5"	MEGAXBIB	MICHELIN
REAR	OPTIONAL	380/90R46	15"	SPRAYBIB	MICHELIN
REAR	NARROW	320/90R50	12.6"	ULTRA SPRAYER	GOODYEAR

Standard tires adjust crop clearance to 42". Optional tires (Front: 380/80R38, Rear: 380/90R46) adjust crop clearance to 48".

AS740, AS1040, AS1240

OPTION	TYPE	SIZE	WIDTH	SERIES	MANUFACTURER
FRONT	STANDARD	380/80R38	15"	AGRIBIB	MICHELIN
FRONT	NARROW	320/85R38	12.6"	DT800	GOODYEAR
REAR	STANDARD	380/90R46	15"	SPRAYBIB	MICHELIN
REAR	NARROW	320/90R50	12.6"	ULTRA SPRAYER	GOODYEAR
REAR	FLOTATION	620/70R42	24.4"	MEGAXBIB	MICHELIN
REAR	FLOTATION	800/65R32	31.5"	MEGAXBIB	MICHELIN
REAR DUAL	STANDARD	380/90R46	15"	SPRAYBIB	MICHELIN
REAR DUAL	NARROW	320/90R50	12.6"	ULTRA SPRAYER	GOODYEAR

All brand or product names are or may be trademarks of, and are used to identify products and services of their respective owners or its subsidiaries and divisions in the U.S. and/or other countries. All specifications are subject to change without notice.

