



WHY RUN WITH APACHE?

THE APACHE MODEL AS1220 PLUS II SPRAYER

Comfort. Speed. Accuracy. Efficiency. That's exactly what you get from every Apache sprayer. They're built to handle the everyday (and not-so-everyday) field conditions with a higher standard of comfort and performance. Because all we do is build sprayers, we're 100% focused on building the best sprayers in the industry, backed by the best warranty in the industry.

The Apache AS1220 Plus II sprayer is the highest-capacity model in the lineup. It features a 1,200-gallon tank so you spend less time refilling and more time spraying. Its mechanical drive makes it simple to operate and maintain, while nimble enough to work in field conditions competitive sprayers can't. It's 15,050 pounds lighter than a Deere R4045, reducing yield-robbing compaction. When the days are long, its 35 mph road speed will get you to the next field (or home) faster. For those who require more horsepower, the AS1220 Plus II model features a 275 hp engine.

Limited supply of AS1220 sprayers with Tier 3 engines available at significant discount versus Tier 4 engine models. Ask your Apache dealer for details.

UNIQUE FEATURES OF THE AS1220 PLUS II

Tank Capacity

1,200 gallons

Transmission

ZF Power Shift, 6-speed with lock-up torque converter

Engine

Tier 3 275 hp
Cummins engine

Top Road Speed

35 MPH

Weight

20,300 lbs (approx. dry weight)

Crop Clearance

50" clearance with 18" drop box all-gear final drives



THE APACHE MODEL AS1220 PLUS II SPRAYER

Specifications

Tank Capacity	1,200 gallons
Transmission	ZF Power Shift, 6-speed with lock-up torque converter
Engine	Tier 3 275 hp Cummins engine
Top Road Speed	35 MPH
Weight	20,300 lb (approximate dry weight)
Crop Clearance	50" with 18" drop box all-gear final drives
Fuel Capacity	100 gallons
Suspension	Patented independent hydraulic
Brakes	Fully-enclosed, self-adjusting, internal wet disc brakes
Front Tires	380/80R38 (narrow and semi-float options available)
Rear Tires	380/90R46 (narrow, semi-float and full-float options available)
Transport Width and Height	144" maximum
Overall Length	290" maximum
Booms	Straight 90' or 100' or 60'/90' custom boom Straight 120' or 132'
Product Pump	HYPRO® hydraulically-driven centrifugal product pump
Rinse Tank	100 gallons
Cab	ET custom pressurized state-of-the-art interior and console
Precision Application Equipment	Raven Hawkeye™ or Trimble (factory installed)

All model year 2017 Apache sprayers are available with optional ISOBUS-ready wiring in lieu of factory installed field computers. Refer to your specific precision agriculture product documentation for compatibility information. Equipment Technologies factory installs all field computers using CAN bus wiring and protocols.

