

EquipmentWatch.

**Highest  
Retained Value  
Award™**  
2018

**3x**  
Winner



# AS1230

## THE APACHE MODEL AS1230 SPRAYER

Comfort. Speed. Accuracy. Efficiency. That's exactly what you get from every Apache Sprayer. They're built to handle the everyday (and not-so-everyday) field conditions with a higher standard of comfort and performance. Because all we do is build sprayers, we're 100% focused on building the best sprayers in the industry.

The Apache AS1230 Sprayer is the highest-capacity model in the lineup. It features a 1,200-gallon tank so you spend less time refilling and more time spraying. Its mechanical drive makes it simple to operate and maintain, while nimble enough to work in field conditions competitive sprayers can't. It's 14,350 pounds lighter than a Deere R4045, reducing yield-robbing compaction. When the days are long, its 35 mph road speed will get you to the next field (or home) faster.

### UNIQUE FEATURES OF THE AS1230

**Tank Capacity**

1,200 gallons

**Transmission**

ZF Powershift, 6-speed with lock-up torque converter

**Engine**

Tier 4F 260 hp  
Cummins engine

**Top Road Speed**

35 mph

**Weight**

21,000 lbs (approximate dry weight)

**Crop Clearance**

50" clearance with 18" drop box all-gear final drives

**APACHE**   
by  
**SPRAYERS**

Learn more about the advantages of running with Apache! Visit your local Apache dealer or [apachesprayers.com](http://apachesprayers.com).

 877-398-6164

# THE APACHE MODEL AS1230 SPRAYER

TANK	TANK CAPACITY	1,200 gal
ENGINE & DRIVETRAIN	TRANSMISSION	ZF Powershift, 6-speed with lock-up torque converter
	CUMMINS ENGINE	Tier 4F 260 hp AS1230
	TOP ROAD SPEED	35 mph
	FUEL CAPACITY	90 gal
CHASSIS, SUSPENSION & TIRES	WEIGHT	21,000 lbs (approximate dry weight)
	CROP CLEARANCE	50" clearance with 18" drop box all-gear final drives
	DEF TANK	5 gal
	SUSPENSION	Patented independent hydraulic
	AXEL WIDTH	120" fixed 120" - 160" adjustable
	BRAKES	Fully enclosed, self-adjusting, internal wet disc brakes
	FRONT TIRES REAR TIRES	Michelin® 380/80R38 (narrow and semi-float options available)
	TRANSPORT WIDTH AND HEIGHT	144" maximum
	OVERALL LENGTH	290" maximum
SPRAY OPTIONS	BOOMS	ET Custom Boom Straight 90' or 100' or 60'/90' Pommier Straight 100', 120' or 132'
	PRODUCT PUMP	Hypro® hydraulically-driven centrifugal product pump
	RINSE TANK	100 gal
CAB	ET CUSTOM PRESSURIZED	State-of-the-art interior and console
	PRECISION APPLICATION EQUIPMENT	Raven Hawkeye™

All model year 2018 Apache Sprayers are available with optional ISOBUS-ready wiring in lieu of factory installed field computers. Refer to your specific precision agriculture product documentation for compatibility information. Equipment Technologies factory installs all field computers using CAN-BUS wiring and protocols.

Equipment Technologies reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. All brand or product names are or may be trademarks of, and are used to identify products and services of, their respective owners or its subsidiaries and divisions, in the U.S. and/or other countries. All specifications are subject to change without notice.



Learn more about the advantages of running with Apache! Visit your local Apache dealer or [apachesprayers.com](http://apachesprayers.com).

877-398-6164