

# AS1040



## THE BEST SELLING APACHE SPRAYER

Comfort. Speed. Accuracy. Efficiency. That's exactly what you get from every Apache Sprayer. They're built to handle the toughest field conditions with a higher standard of comfort and performance. Because all we do is build sprayers, we're 100% focused on building the best sprayers in the industry.

The Apache AS1040 is easily the most popular sized model in our lineup as its 1,000-gallon tank fits perfectly for almost any farming operation size. Get moving and spray where and when you need to.

### Lightweight

The AS1040 is engineered lightweight at just 20,000 pounds. That means better fuel economy, reduced compaction and a lower price.

### Perfect Size

This model offers a turning radius of 18' and a wheel base of 15' — perfect for tight-fit areas.

### Reliable

According to a statistical analysis conducted at the Indiana University Kelley School of Business, the Apache 1000 Series Sprayer retains an average of 72% of its value after five years — one of the highest in the farm equipment industry.

In fact, *EquipmentWatch*™ recognized Apache Sprayers as the "Highest Retained Value" in the farm equipment industry for three consecutive years (2016, 2017 and 2018).

### Unique Features of the AS1040

**Tank Capacity**  
1,000 gallons

**Transmission**  
ZF Powershift, 6-speed with lock-up torque converter

**Engine**  
Cummins Tier 4F 225 hp (rated)

**Top Road Speed**  
35 mph

**Weight**  
20,000 lbs (approximate dry weight)

**Crop Clearance**  
JCB 42" with planetary final drive  
50" with 18" drop box all-gear final drives (optional)



**APACHE** **ET**  
SPRAYERS

Learn more about the advantages of running with Apache! Visit your local Apache dealer or [apachesprayers.com](http://apachesprayers.com).

877-398-6164

# THE APACHE AS1040 SPRAYER

CHASSIS, SUSPENSION & TIRES	TANK CAPACITY	1,000 gal
	WEIGHT (APPROXIMATE DRY WEIGHT)	20,000 lbs
	AXLE WIDTH	120" fixed 120"-160" adjustable (with optional 50" clearance only)
	TURNING RADIUS	18'
	WHEEL BASE	15'
	FRONT TIRES (STANDARD)	Michelin® 380/80R38
	REAR TIRES (STANDARD)	Michelin 380/90R46
	CROP CLEARANCE	42" with JCB planetary final drive 50" with 18" drop box all-gear final drives (optional)
SPRAY OPTIONS	BOOMS	ET Custom Boom (Steel) Straight 90', 100' or 60'/90' Pommier (Aluminum) Straight 100', 120' or 132'
	RINSE TANK	100 gal
ENGINE & DRIVETRAIN	RATED HORSEPOWER	225 hp
	DRIVELINE EFFICIENCY	90%
	PTG: HP PER 1,000 lbs	10.1
	FUEL TANK CAPACITY	90 gal
	SUSPENSION	Patented independent hydraulic
	TOP ROAD SPEED	35 mph
	TRANSMISSION	ZF Powershift, 6-speed with lock-up torque converter
	ENGINE	Cummins Tier 4F 225 hp (rated)

## COMMON FEATURES ON ALL APACHE SPRAYER MODELS

CHASSIS & SUSPENSION	BRAKES	Fully enclosed, self-adjusting, internal wet disc brakes
	DEF TANK	5 gal
	TRANSPORT WIDTH & HEIGHT	144" maximum
	OVERALL LENGTH	290" maximum
CAB	PRECISION APPLICATION EQUIPMENT	Raven Viper® 4+, Hawkeye®, AccuBoom™, AutoBoom® XRT, Autofold, UltraGlide and RS1™ Advanced Steering
	ET CUSTOM PRESSURIZED	State-of-the-art interior and console



### FIVE-YEAR LIMITED WARRANTY

Equipment Technologies warrants every new Apache Sprayer to be free from defects in materials and workmanship for a period of five years or 2,000 hours, whichever occurs first. The first two years of warranty includes bumper-to-bumper coverage (some exclusions apply), with the following three years covering parts only.

All model year 2020 Apache Sprayers are available with optional ISOBUS-ready wiring in lieu of factory installed field computers. Refer to your specific precision agriculture product documentation for compatibility information. Equipment Technologies factory installs all field computers using CAN-BUS wiring and protocols.

Equipment Technologies reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. All brand or product names are or may be trademarks of, and are used to identify products and services of, their respective owners or its subsidiaries and divisions, in the U.S. and/or other countries. All specifications are subject to change without notice.



Learn more about the advantages of running with Apache! Visit your local Apache dealer or [ApacheSprayers.com](http://ApacheSprayers.com).

877-398-6164