

AS640



PERFORMANCE AND RELIABILITY AT A PRICE YOU CAN AFFORD

The Apache AS640 is compact, lightweight, agile — and the most affordable self-propelled sprayer in the industry. The AS640 is built for the farmer who wants to upgrade to a self-propelled and spray on their own or the larger producer who needs an agile extra sprayer. This model features a 650-gallon tank, 4-speed JCB Powershift transmission, a powerful 163 hp Cummins engine and a 90- or 120" axle design. The AS640 sprayer is everything that is great about Apache, but in a compact package. Just like all Apache Sprayer models, the AS640 is fuel efficient, reliable and provides mind-blowing operator comfort with a state-of-the-art cab and a simple user interface.

Lightweight

The AS640 is the lightest sprayer made at just 16,900 pounds. That means better fuel economy, reduced compaction and a lower price.

Perfect Size

This model offers a turning radius of 17' 2" and a wheel base of 13' 8" — perfect for tight-fit areas.

Reliable

According to a statistical analysis conducted at the Indiana University Kelley School of Business, the Apache 1000 Series Sprayer retains an average of 72% of its value after five years — one of the highest in the farm equipment industry.

In fact, *EquipmentWatch*™ recognized Apache Sprayers as the "Highest Retained Value" in the farm equipment industry for three consecutive years (2016, 2017 and 2018).

Unique Features of the AS640

Tank Capacity

650 gallons

Transmission

JCB transmission
Powershift, 4-speed

Engine

Cummins Tier 4F 163 hp (rated)

Top Road Speed

32 mph

Weight

16,900 lbs (approximate dry weight)

Crop Clearance

42" or 48" based on tire
selection with JCB final drives



APACHE by **ET**
SPRAYERS

THE APACHE AS640 SPRAYER

CHASSIS, SUSPENSION & TIRES	TANK CAPACITY	650 gal
	WEIGHT (APPROXIMATE DRY WEIGHT)	16,900 lbs
	AXLE WIDTH	88", 90", 108", 114" or 120" fixed
	TURNING RADIUS	17' 2"
	WHEEL BASE	13' 8"
	FRONT TIRES (STANDARD)	Michelin® 380/85R34
	REAR TIRES (STANDARD)	Michelin 380/80R38
	CROP CLEARANCE	42" or 48" based on tire selection
SPRAY OPTIONS	BOOMS	ET Custom Boom (Steel) Straight 90' or 60'/90' Pommier (Aluminum) Straight 100'
	RINSE TANK	50 gal
ENGINE & DRIVETRAIN	RATED HORSEPOWER	163 hp
	DRIVELINE EFFICIENCY	90%
	PTG: HP PER 1,000 lbs	8.7
	FUEL TANK CAPACITY	80 gal
	SUSPENSION	Active airbag with independent front
	TOP ROAD SPEED	32 mph
	TRANSMISSION	JCB transmission Powershift, 4-speed
	ENGINE	Cummins Tier 4F 163 hp (rated)

COMMON FEATURES ON ALL APACHE SPRAYER MODELS

CHASSIS & SUSPENSION	BRAKES	Fully enclosed, self-adjusting, internal wet disc brakes
	DEF TANK	5 gal
	TRANSPORT WIDTH & HEIGHT	144" maximum
	OVERALL LENGTH	290" maximum
CAB	PRECISION APPLICATION EQUIPMENT	Raven Viper® 4+, Hawkeye®, AccuBoom™, AutoBoom® XRT, Autofold, UltraGlide and RS1™ Advanced Steering
	ET CUSTOM PRESSURIZED	State-of-the-art interior and console



FIVE-YEAR LIMITED WARRANTY

Equipment Technologies warrants every new Apache Sprayer to be free from defects in materials and workmanship for a period of five years or 2,000 hours, whichever occurs first. The first two years of warranty includes bumper-to-bumper coverage (some exclusions apply), with the following three years covering parts only.

All model year 2020 Apache Sprayers are available with optional ISOBUS-ready wiring in lieu of factory installed field computers. Refer to your specific precision agriculture product documentation for compatibility information. Equipment Technologies factory installs all field computers using CAN-BUS wiring and protocols.

Equipment Technologies reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. All brand or product names are or may be trademarks of, and are used to identify products and services of, their respective owners or its subsidiaries and divisions, in the U.S. and/or other countries. All specifications are subject to change without notice.



Learn more about the advantages of running with Apache! Visit your local Apache dealer or [ApacheSprayers.com](https://www.ApacheSprayers.com).

855-979-2984